

EPS® 2420

All-Acrylic Emulsion

MARKET SEGMENT: INDUSTRIAL WOOD COMMON APPLICATIONS: TOPCOAT

EPS® 2420 is a binder for interior and exterior wood applications such as multi-coat, enamels and varnishes with exceptional leveling properties and UV resistance. In-can transparency is a key feature of this product.

PERFORMANCE BENEFITS

- Leveling
- Clear in-can
- Block resistance
- Exterior durability
- Medium hardness
- Flexibility
- Early water and water resistance
- Stackability
- Low water uptake
- High transparency
- Made without APEO surfactants

TYPICAL PROPERTIES

Weight Solids	45.0 +/- 1.0%
Weight/Gallon	8.60 +/- 0.10
рН	7.3 - 8.3
Volume Solids	43.4 +/- 0.7%
MFFT	5° C
Volatile(s)	Water, ammonia, propylene glycol (0.074%)

These typical properties do not represent specifications.

SUGGESTED COALESCING SOVENT(S)

(% Solvent on Binder Solids - Pass 40°F LTC Test)

170 00110111 011 01111101 0011110	1 4.00 10 1 = 10 1000	
DPM	2.50%	
DPnB	2.50%	
Butyl Cellosolve	2.50%	
Butyl Carbitol	2.50%	