

RayCryl® 61

All-Acrylic Emulsion

MARKET SEGMENT: CONSTRUCTION

COMMON APPLICATIONS: SPORT COURTS & FIELD MARKING

RayCryl® 61 is an all-acrylic emulsion designed for exterior durability. Due to low surfactant level in design, this product improves water resistance in coatings. RayCryl® 61 is formulated with high solids, which allows more latitude in developing high-solids coatings.

PERFORMANCE BENEFITS

- Water resistance
- UV durability

TYPICAL PROPERTIES

Weight Solids	60%
Weight/Gallon	8.90
pH	9.0-9.5
Volume Solids	57.3%
MFFT	8° C
Volatile(s)	Water

Questions? Call EPS Customer Service @ 1-800-654-4242 / Email: info@eps-materials.com

4/23/2024

SDS: For details on health, safety and handling information, Safety Data Sheets (SDS) are available at www.epsgca.com.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at <https://www.epsgca.com/galleries/pdfs/salesterms.pdf>.